

ADS-RR SERIES


ADJUSTABLE DUAL SWING RELAY RACK

MAINFRAME Adjustable Dual-Swing Series provides a time-saving, rotating interface, perfect for accessing your equipment. With adjustable depth (18-26") you can be certain that your hardware will fit securely while being conveniently accessible.



Swing-out mounting rails

These 19" mounting rails can be swung-out, providing easy access to install or upgrade equipment.



Adjustable depth

Depth is adjustable from 18-26".

FEATURES

- Accepts standard 19" rackmount equipment
- Easy installation with accessible design
- Attractive powder-coated finish
- **Loading Capacity**
Static loading capacity up to 45kg.
- **Material:**
SPCC cold rolled steel construction
- **Pre-tapped 12-24 mounting rails come with:**
 - 12 x M6 Assembly Screws and Nuts
 - 12-24 Screws and Cage Nuts
 - 6/9/12U: 12 sets 15/18U: 24 sets
 - 4 x Concrete Anchors
- Includes a 3-year limited warranty from MAINFRAME

SPECIFICATIONS

SKU	SIZE	DIMENSIONS W × D × H	LOAD CAPACITY
ADS-RR-6U	6U	524 × 461-664 × 387.70 mm (20.63 × 18.15-26.14 × 15.26 in)	45 kg (99 lbs)
ADS-RR-9U	9U	524 × 461-664 × 521.05 mm (20.63 × 18.15-26.14 × 20.51 in)	45 kg (99 lbs)
ADS-RR-12U	12U	524 × 461-664 × 654.40 mm (20.63 × 18.15-26.14 × 25.76 in)	45 kg (99 lbs)
ADS-RR-15U	15U	524 × 461-664 × 787.75 mm (20.63 × 18.15-26.14 × 31.01 in)	45 kg (99 lbs)
ADS-RR-18U	18U	524 × 461-664 × 921.10 mm (20.63 × 18.15-26.14 × 36.26 in)	45 kg (99 lbs)



ADS-RR-6U



ADS-RR-9U



ADS-RR-12U



ADS-RR-15U



ADS-RR-18U